

## MOSIL SPRAY - 11

### Electrical Contact Cleaner-cum-Lubricant

A blend of solvents and synthetic lubricants formulated to remove the surface contamination and oxidation residues. It is a non-silicone based product thereby eliminating the problems caused by carbon deposits and silicone migration.

#### AREA OF APPLICATION

Electrical connectors, switches, sliding and rotary tuners, potentiometers, test instruments, rocker / push-pull switches, relays, circuit breakers, transformers, switchgears, Terminals, Transformers, motors, generators, control instruments, communication assemblies, starters, solenoids, Capacitors, Fuse Boxes, Ignition systems etc.

#### BENEFITS

- ➔ Removes surface contamination and oxidation from contact surfaces.
- ➔ Rapid solvent evaporation ensuring faster return to normal operation.
- ➔ Prevents capacitance, resistance and frequency deviations, erratic high and low setting spots, sparking and tracking.
- ➔ Compatible with Plastics such as ABS, Nylon, Polycarbonate etc.
- ➔ LPG propellant.

PACKING: 500ml Aerosol Spray

Owing to evolving packaging solutions, user is requested to kindly check the availability of a specific pack size prior to standardization.



**CHARACTERISTICS**

**TYPICAL VALUES**

1. Appearance	Liquid
2. Base	Solvent / Synthetic
3. Colour	Transparent
4. Specific Gravity	0.75 ± 0.1 (bulk)
5. Flash Point (of Oil)	> 200° C
6. Odour	Faint (characteristics)
7. Copper Strip Corrosion	Negative
8. Propellant	Blend of Propane & Butane
9. Contents	500ml when packed
10. Container	Aerosol tin with 25mm valve and actuator

*Material Safety Information required for safe usage of this product may not be included in this product bulletin and may be sought by contacting MOSIL. Users are advised to go through the Material Safety Data Sheet (MSDS) of this product prior to application / usage of this product.*

*All statements and information contained in this document are based on the laboratory testing and user experience on actual applications. Owing to the exhaustive possibility of application for which this product may be used and the variety of equipments, performance parameters, environmental conditions and unpredictable human factors, we strongly recommend that this product be tested on the actual application prior to its standardization. All information contained herewith is offered in good faith but without any expressed or implied warranty. This Product Bulletin may already have been revised considering the availability of raw components, legislation, user experience & expectations and enhancement of knowledge of the development team of MOSIL. Users are requested to kindly seek the latest version of this product bulletin by contacting MOSIL. Information provided in this Product Bulletin is based on the generalised expectations and requirements of users. Additional information for this product may also be sought by contacting MOSIL.*

Rev 02, Issue 00

**Mosil Lubricants Private Limited**

**Technical Services Dept:** "ANIRA" Plot No. A-791/3, MIDC Khairne, Navi Mumbai - 400710. INDIA  
T: +91 22 2464 0500 /0501 | F: +91 22 2778 8505 | E: corporate@mosil.com | W: www.mosil.com  
Regd Office:166/1, KALANIDHI, Sion(West), Mumbai - 400 022 | CIN # U23200 MH 2000 PT C124177

